

surveillance-video.com
do-it-yourself-surveillance

387, Canal Street, Manhattan, NY 10013
Email: info@surveillance-video.com



1.800.955.5201



1.212.431.2622

5.8GHz Dual Diversity 480 Line 200 Floor Elevator Video System



VIDEOCOMM - 5.8GHz Dual Diversity 480 Line 200 Floor Elevator Video System

Product Code	EV-L2R5803
Description	<p>The EV-L2R5803 from Videocomm is a 5.8GHz Dual Diversity 480 Line 200 Floor Elevator Video System that comes with a revolutionary pre-configured plug and play design. The EV-L2R5803 is the industry's only wireless elevator camera system that delivers real-time, DVD quality encrypted digital video up to 200 floors. It features a revolutionary pre-configured plug-and-play design.</p> <p>The EV-L2R5803 system does not require software, setup or programming, and requires minimum installation time and delivers maximum results. This wireless system can be chosen for most extreme elevator surveillance applications. The EV-L2R5803 wireless video system is complete with all accessories including "easy connect" power and video inputs, 25' video / power cable and a rugged tamper-proof corner mount SONY camera.</p>
Specifications	Values
Model	EV-L2R5803
Operating Frequency	Dual Radio 5.725GHz - 5.875GHz @ 20MHz Bandwidth
Frequency Control	Automatic Channel Selection
Data Rate	6 mbps - 54 mbps
Video Compression Format	Hardware Based MPEG-4
Frame Rate	30fps NTSC / 25fps PAL
Video Resolution	720 x 480 NTSC / 720 x 576 PAL
Radiated Power	450mW
Range	200 Floors
Antenna Type	6 x 3dBi Omni-Directional Rubber Duck Antennas
Receiver Sensitivity	54 mbps @ -72dBm to 6 mbps @ -90dBm
Video Connector	BNC Male 75 OHMS @ 1 Volt Peak-to-Peak
Temperature Range	-40°F to +160°F
Power Supply Included	Switching 12VDC @ 2 Amps - CEC Class IV
Current Consumption	0.8 Amps
Operating Voltage	12 - 30 Volts AC or DC
Surge Protection	ESD Surge / Lightning Protected up to 1,500 Watts

Enclosures	Rugged IP-67 Rated All Weather Enclosure
Mounting Brackets Included	Two Universal Wall / Pole Mount - # BRK-250
Camera Construction	Vandal Proof IP-66 Rated Enclosure
Camera Current Consumption	<130mA
Camera Dimensions	8" x 8" x 3"
Camera Resolution	480 Lines
Camera Type	Corner Mount 1/3" Color SONY CCD
Camera Weight	1,650g or 3.6lbs
Electronic Shutter	1/50 ~ 1/10,000 Sec.
Lens Type	Board lens 2.8mm @F2.0
Minimum Illumination	0.4 Lux / F1.2
S/N Ratio	>48dB (AGC Off)
White Balance	Automatic
Dimensions	7.0" x 7.0" x 4.5" Each Enclosure

• Features

- 64 Bit encrypted data stream (optional 128 bit)
- Revolutionary pre-configured plug & play design
- Transmits Real-Time DVD quality video up to 200 floors
- Digital immunity to signal interference
- Industry leading 5-tier input power management system
- Automatic system pairing and on screen status display
- No maintenance or inspections required
- FCC & IC approved for license free use

Terms & Policies:

Pricing:

We make every effort to provide you the most accurate, up-to-the-minute information, but mistakes do occur, and we must reserve the right to make corrections, adjustments or changes without notice. If you have ordered an item that is subject to a price increase, we will hold your order and inform you of the increase.

Availability:

The availability information presented on our site is the best, most current information we have, but errors do occur, and this information does not constitute a guarantee or promise of availability. If a product you have ordered is not available for shipment, we will do our best to let you know. Anticipated delivery dates are dependent upon our suppliers and other factors beyond our control, and are subject to change.

Payment:

At this time, Surveillance-Video.com accepts the following payment methods: American Express, VISA & Master Card, Discover Card, Paypal.

All credit card orders are subject to verification and approval by the card-issuing bank. For your protection, credit card orders shipped to an address other than your billing address may require additional verification. Surveillance-video.com reserves the right to contact you by email or telephone to request additional identification. We may reject orders if the verification fails.

Surveillance-Video.com

387 Canal Street

Manhattan, NY 10013

Tel. 1.800.955.5201

Fax. 1.212.431.2622

info@Surveillance-Video.com