

**surveillance-video.com**  
**do-it-yourself-surveillance**

387, Canal Street, Manhattan, NY 10013  
Email: [info@surveillance-video.com](mailto:info@surveillance-video.com)



**1.800.955.5201**



**1.212.431.2622**

## **ICD-68 - High Performance Black & White Super Dome Camera**



## **IKEGAMI - ICD-68 - High Performance Black & White Super Dome Camera**

|                              |  |
|------------------------------|--|
| Product Code                 | <b>ICD-68</b>  |
| Description                  | The ICD-68 from Ikegami is a high performance black & white super dome camera that is designed to be modest and not conflict with the aesthetic properties of stores and commercial/residential areas. The ICD-68 dome camera can be recessed into the ceiling, showing only dome portion of the camera with optional ceiling mount kit, or surface mounted as is on to ceiling. The ICD-68 comes with built-in vari-focal lens that is equipped with a vari-focal auto iris lens as standard, which helps to view angle adjustment. |
| <b>Specifications</b>        | <b>Values</b>  |
| Model                        | ICD-68   |
| Imaging Device               | 1/3" Interline Transfer CCD  |
| Total No. of Pixels          | 512 (H) x 492 (V) lines, approx. 250,000 pixels  |
| Sensing Area                 | 4.8 (H) x 3.6 (V) mm   |
| Scan System                  | EIA, 2:1 interlace   |
| Sync System                  | Line lock (phase adjustable)   |
| Vertical Sync Frequency      | 60Hz   |
| Horizontal Sync Frequency    | 15.75kHz   |
| Video Output                 | (1) VIDEO OUTPUT: VS1.0Vp-p/75 ½<br>(2) MON. OUTPUT: VS1.0Vp-p/75 ½  |
| Horizontal Resolution        | 380 TV lines   |
| S/N Ratio                    | 48 dB (at standard illumination, weight-ON)  |
| Minimum Illumination         | 0.3 lux (30 IRE) Wide Angle Side<br>1.4 lux (50 IRE) Wide Angle Side   |
| Backlight Compensation (BLC) | ON/OFF switchable, level adjustable  |
| AGC                          | Fixed at ON  |
| Fixed at ON                  | Focal distance: F4.0 - 9.0 mm<br>Iris control: Auto iris control function<br>Focal depth: ° ~ 0.5 m  |
| Angle Adjustment             | Horizontal: 0° - 360°(in mounting),<br>± 30° (in fine adjustment)<br>Vertical: 7° - 166°   |
| Working Ambient Temperature  | -10 to +50°C   |
| Current Consumption          | Approx. 1.7W   |
| Power Supply                 | AC24V ± 10%, 60Hz  |
| Outer Dimensions             | ø130 x H127 mm<br>(Projections and accessories are excluded.)  |
| Weight                       | Approx. 630g   |

|   |
|---|
| <ul style="list-style-type: none"><li>• <b>Features</b></li></ul> |
|---|

- |   |
|---|
| <ul style="list-style-type: none"><li>• Comes with High Sensitivity.</li></ul>      |
| <ul style="list-style-type: none"><li>• Offers resolution of 380TV Lines.</li></ul> |
| <ul style="list-style-type: none"><li>• Backlight compensation.</li></ul>           |
| <ul style="list-style-type: none"><li>• Mirror image function.</li></ul>            |
| <ul style="list-style-type: none"><li>• Includes line lock function.</li></ul>      |
| <ul style="list-style-type: none"><li>• Integration with vari-focal lens.</li></ul> |

**Terms & Policies:**

**Pricing:**

We make every effort to provide you the most accurate, up-to-the-minute information, but mistakes do occur, and we must reserve the right to make corrections, adjustments or changes without notice. If you have ordered an item that is subject to a price increase, we will hold your order and inform you of the increase.

**Availability:**

The availability information presented on our site is the best, most current information we have, but errors do occur, and this information does not constitute a guarantee or promise of availability. If a product you have ordered is not available for shipment, we will do our best to let you know. Anticipated delivery dates are dependent upon our suppliers and other factors beyond our control, and are subject to change.

**Payment:**

At this time, Surveillance-Video.com accepts the following payment methods: American Express, VISA & Master Card, Discover Card, Paypal.

All credit card orders are subject to verification and approval by the card-issuing bank. For your protection, credit card orders shipped to an address other than your billing address may require additional verification. Surveillance-video.com reserves the right to contact you by email or telephone to request additional identification. We may reject orders if the verification fails.

**Surveillance-Video.com**

387 Canal Street

Manhattan, NY 10013

Tel. 1.800.955.5201

Fax. 1.212.431.2622

[info@Surveillance-Video.com](mailto:info@Surveillance-Video.com)