

## Videolarm - MR5CN-9 - Indoor Recessed Dome With PTZ IP Camera System



The VIDEOLARM introduces MR5CN-9 an indoor recessed, clear dome with PTZ IP camera system and pendant mount that offers MPEG-4 & MJPEG video compression format with 30/25 FPS video refresh rate at Full D1 resolution. The MR5CN-9 is perfect for perimeter security, parking lots, and airports or anyplace where day/night capabilities are essential. The MR5CN-9 features auto focus, high-resolution, true day/night camera which has a .02 lux minimum illumination when the IR filter is removed. The camera offers 230x zoom (23x optical and 10x digital) with 360° continuous rotation at 180° or 360°/sec. The MR5CN-9 is capable of 18 presets and auto tour, up to two minutes of recordable pattern, and a host of other features.

### FEATURES

- MPEG-4 & MJPEG video compression format.
- Adjustable video compression.
- Offers High Resolution of 470TV Lines.
- Digital zoom on/off.
- 16 user selectable privacy zones.
- Automatic flip-over

### SPECIFICATIONS

Camera Imager	¼" interline transfer CCD
Signal Format	NTSC, PAL
Horizontal Resolution	470 TVL - NTSC
Digital Zoom	10x (230x with optical zoom)
Angle of View	54 degrees (wide end) to 2.5 degrees (tele end)
Minimum Illumination	.02 Lux
Signal to Noise Ratio	50 dB
Shutter Speed	Auto/Manual (manual ½s-1/30000s)
White Balance	Auto/Manual
Iris Control	Auto/Manual
Backlight Compensation	On/Off
Panning	360° Continuous pan rotation
Tilting	2° to -90°
Panning Speed	120°/sec, 0.5°-80°/sec manual oper.
Tilting Speed	120°/sec, 0.5°-80°/sec manual oper.
Preset Accuracy	+/- .05 degree
Construction Body	Stamped metal
Dome	Cell-cast acrylic
Max camera length	5"
Trim Ring	ABS plastic
Input Voltage	24 vac
Operating Temperature	32° F to 120° F (0° C to + 49° C)
Video Connector	Indoor coax output, RS422 or RS485 communications
Power Consumption	24vac, 24watts (va)
Dimensions (h*w*d)	8.54 x 8.38 x 8.38" (217 x 213 x 213mm)
Weight	10 lbs / 4.54 kg