

surveillance-video.com
do-it-yourself-surveillance

387, Canal Street, Manhattan, NY 10013
Email: info@surveillance-video.com



1.800.955.5201



1.212.431.2622

MR5CN-9 - Indoor Recessed Dome With PTZ IP Camera System



Videolarm - MR5CN-9 - Indoor Recessed Dome With PTZ IP Camera System

Product Code	MR5CN-9
Description	<p>The VIDEOLARM introduces MR5CN-9 an indoor recessed, clear dome with PTZ IP camera system and pendant mount that offers MPEG-4 & MJPEG video compression format with 30/25 FPS video refresh rate at Full D1 resolution. The MR5CN-9 is perfect for perimeter security, parking lots, and airports or anyplace where day/night capabilities are essential.</p> <p>The MR5CN-9 features auto focus, high-resolution, true day/night camera which has a .02 lux minimum illumination when the IR filter is removed. The camera offers 230x zoom (23x optical and 10x digital) with 360° continuous rotation at 180° or 360°/sec. The MR5CN-9 is capable of 18 presets and auto tour, up to two minutes of recordable pattern, and a host of other features.</p>
Specifications	Values
Model	MR5CN-9
Camera Imager	1/4" Interline transfer CCD
Signal Format	NSTC, PAL
Horizontal Resolution	470 TVL - NTSC
Digital Zoom	10x (230x with optical zoom)
Angle of View	54 degrees (wide end) to 2.5 degrees (tele end)
Minimum Illumination	.02 Lux
Signal to Noise Ratio	50dB
Shutter Speed	Auto/Manual (manual 1/2s - 1/30,000s)
White Balance	Auto/Manual
Iris Control	Auto/Manual
Backlight Compensation	On/Off
Panning	360° Continuous pan rotation
Tilting	2° to -90°
Panning Speed	120°/sec, 0.5°-80°/sec manual operation
Tilting Speed	120°/sec, 0.5°-80°/sec manual operation
Preset Accuracy	+/- .05 degree
Body Construction	Stamped metal
Dome	Cell-cast acrylic

Max camera length	5"
Trim Ring	ABS plastic
Input Voltage	24 vac
Operating Temperature	32° F to 120° F (0° C to + 49° C)
Video Connector	Indoor coax output, RS422 or RS485 communications
Power Consumption	24vac, 24watts (va)
Dimensions (h*w*d)	8.54 x 8.38 x 8.38" (217 x 213 x 213mm)
Weight	10 lbs / 4.54 kg

● Features

- MPEG-4 & MJPEG video compression format.
- Adjustable video compression.
- Offers High Resolution of 470TV Lines.
- Digital zoom on/off.
- 16 user selectable privacy zones.
- Automatic flip-over

Terms & Policies:

Pricing:

We make every effort to provide you the most accurate, up-to-the-minute information, but mistakes do occur, and we must reserve the right to make corrections, adjustments or changes without notice. If you have ordered an item that is subject to a price increase, we will hold your order and inform you of the increase.

Availability:

The availability information presented on our site is the best, most current information we have, but errors do occur, and this information does not constitute a guarantee or promise of availability. If a product you have ordered is not available for shipment, we will do our best to let you know. Anticipated delivery dates are dependent upon our suppliers and other factors beyond our control, and are subject to change.

Payment:

At this time, Surveillance-Video.com accepts the following payment methods: American Express, VISA & Master Card, Discover Card, Paypal.

All credit card orders are subject to verification and approval by the card-issuing bank. For your protection, credit card orders shipped to an address other than your billing address may require additional verification. Surveillance-video.com reserves the right to contact you by email or telephone to request additional identification. We may reject orders if the verification fails.

Surveillance-Video.com

387 Canal Street

Manhattan, NY 10013

Tel. 1.800.955.5201 Fax. 1.212.431.2622

info@Surveillance-Video.com

<http://www.surveillance-video.com>