

**surveillance-video.com**  
**do-it-yourself-surveillance**

387, Canal Street, Manhattan, NY 10013  
Email: [info@surveillance-video.com](mailto:info@surveillance-video.com)



**1.800.955.5201**



**1.212.431.2622**

## **MR5CS-9 - 5" Indoor Dome PTZ Camera System**



**Videolarm - MR5CS-9 - 5" Indoor Dome PTZ Camera System**

Product Code	<b>MR5CS-9</b>
Description	<p>The VIDEOLARM introduces MR5CS-9 a 5" Indoor Dome PTZ Camera System with astonishing capabilities like auto focus, high-resolution, true day/night camera which has a .02 lux minimum illumination when the IR filter is removed. The MR5CS-9 camera offers 230x zoom (23x optical and 10x digital) with 360° continuous rotation at 180° or 360°/sec.</p> <p>This unit is capable of 24 presets and auto tour, up to two minutes of recordable pattern, and a host of other features. The MR5CS-9 is perfect for perimeter security, parking lots, and airports or anyplace where day/night capabilities are essential. It includes recessed ceiling mount with clear dome. The MR5CS-9 provides an opaque liner with pre-cut viewing window is standard and will hide the direction of the camera in both the clear and tinted domes.</p>
<b>Specifications</b>	<b>Values</b>
Model	MR5CS-9
Camera Imager	1/4" Interline transfer CCD
Signal Format	NSTC, PAL
Horizontal Resolution	470 TVL - NTSC
Digital Zoom	10x (230x with optical zoom)
Angle of View	54 degrees (wide end) to 2.5 degrees (tele end)
Minimum Illumination	.02 Lux
Signal to Noise Ratio	50dB
Shutter Speed	Auto/Manual (manual 1/2s - 1/30,000s)
White Balance	Auto/Manual
Iris Control	Auto/Manual
Backlight Compensation	On/Off
Panning	360° Continuous pan rotation
Tilting	2° to -90°
Panning Speed	120°/sec, 0.5°-80°/sec manual operation
Tilting Speed	120°/sec, 0.5°-80°/sec manual operation
Preset Accuracy	+/- .05 degree
Body Construction	Stamped metal

Dome	Cell-cast acrylic
Max camera length	5"
Trim Ring	ABS plastic
Input Voltage	24 vac
Operating Temperature	32° F to 120° F (0° C to + 49° C)
Video Connector	Indoor coax output, RS422 or RS485 communications
Power Consumption	24vac, 24watts (va)
Dimensions (h*w*d)	8.54 x 8.38 x 8.38" (217 x 213 x 213mm)
Weight	10 lbs / 4.54 kg

### • Features

- Integral multi-protocol receiver/driver
- Automatic flip-over.
- Digital zoom on/off.
- Software programmable pan and tilt limits.
- Compass heading display.
- Protection against Brown Out.
- 16 user selectable privacy zones.
- On-board temperature sensor.

### Terms & Policies:

#### **Pricing:**

We make every effort to provide you the most accurate, up-to-the-minute information, but mistakes do occur, and we must reserve the right to make corrections, adjustments or changes without notice. If you have ordered an item that is subject to a price increase, we will hold your order and inform you of the increase.

#### **Availability:**

The availability information presented on our site is the best, most current information we have, but errors do occur, and this information does not constitute a guarantee or promise of availability. If a product you have ordered is not available for shipment, we will do our best to let you know. Anticipated delivery dates are dependent upon our suppliers and other factors beyond our control, and are subject to change.

**Payment:**

At this time, Surveillance-Video.com accepts the following payment methods: American Express, VISA & Master Card, Discover Card, Paypal.

All credit card orders are subject to verification and approval by the card-issuing bank. For your protection, credit card orders shipped to an address other than your billing address may require additional verification. Surveillance-video.com reserves the right to contact you by email or telephone to request additional identification. We may reject orders if the verification fails.

**Surveillance-Video.com**

387 Canal Street

Manhattan, NY 10013

Tel. 1.800.955.5201 Fax. 1.212.431.2622

[info@Surveillance-Video.com](mailto:info@Surveillance-Video.com)